



Superior Handling Equipment has manufactured the American-made Speed-Lift[™] for over 40 years. It's the only dock lift that utilizes a robust cantilever-motion design and Automatic Folding Ramps to safely and quickly load/unload trucks. The company's focused effort on this lift's development has culminated in a product line that incorporates maximum safety, productivity, and flexibility with its standard features and customizable options, all of which reinforce its durability, reliability, and operational efficiency.

Speed-Lift Product Lines	Configuration	Capacities (LBS)	Standard Platform Sizes (W x L)	Applications
Silver <10,000 LBS		5,000 6,000 8,000	60" x 84" 60" x 96" 60" x 120" (68" for 8,000) 96" max width	Hand Carts, Manual or Powered Pallet Jacks
Gold 10,000 – 15,000 LBS		10,000 12,000 15,000	68" x 120" 68" x 150" 68" x 168" 96" max width	Powered Pallet Jacks, Small Forklifts
<i>Platinum</i> 20,000 – 25,000 LBS		20,000 25,000	68" x 168" 68" x 216" 68" x 252" 96" max width	Large Forklifts and Other Heavy Loads
<i>Mobile</i> 6,000 LBS		6,000	54" x 96"	Hand Carts, Manual or Powered Pallet Jacks

The **Speed-Lift** is available with 10 standard platform sizes and 8 lifting capacities ranging from 5,000 to 25,000 lbs. All lifts are custom-built according to each customer's specific needs with options including side off-loading configurations, extra wide platform sizes, and other customizations to accommodate every material handling need.

The **Mobile Speed-Lift** is a street legal, towable lift that loads/ unloads trucks without the need for a dock and accommodates vehicles without lift gates. This self-contained, selfpowered diesel lift is ANSI compliant and NATM certified for towing by standard truck or SUV while transporting up to 2,000 pounds of cargo. It conforms to all applicable US Federal Motor Vehicle Safety Standards (FMVSS) in place at the date of manufacture.





STANDARD FEATURES

- Dual operator controls
- Truck Bumper Protection System
- Platform Locking Pin to facilitate maintenance
- Pressure relief valve on hydraulic system
- Proportional speed control with feathering capability
- Ground Anchor Impact and Restraint System
- Safety flow limiters on each cylinder to prevent
- platform free-fall
- Integral stabilization jacks
- 208/230 VAC 3Ø

AVAILABLE OPTIONS

- 460/480 VAC 3Ø, 208/230 VAC 1Ø, Gasoline
- Extended Bridge lengths up to 72"
- EZ Install Lifts when restricted access
- Side-Off Platform (Left or Right)
- Wall and Floor Anchors
- Extended Ramp lengths up to 52"
- Lower Opening Bridge
- Lateral Track Mobility service multiple bays
- Platform Weathershield
- Ramp Winch
- Embedded Scale


INDUSTRY-LEADING WARRANTY & SUPPORT


- 5-year Parts & 2-year Labor (non-Mobile)
- 15-year Frame Warranty (non-Mobile)
- 1-year Parts & Labor Mobile
- Extended Warranty Available
- Preventative Maintenance Programs
- Online Training Videos

A WORLD OF APPLICATIONS



RETAIL WAREHOUSES AGRICULTURE MILITARY CONSTRUCTION HOSPITALS SCHOOLS AIRPORTS DISTRIBUTION EMERGENCY MGMT LOGISTICS





www.superiorlifts.com